



**GARUDA**  
**LUBRICANTS**

## **GARUDA HYPERLINE 10W-40 SN (Fully Synthetic)**

### **Product description**

Garuda HYPERLINE is a fully synthetic engine oil formulated with premium base oils and advanced additives. It delivers excellent wear protection, low volatility, and reliable engine cleanliness for gasoline engines, including turbocharged and naturally aspirated types.

### **Applications**

Ideal for gasoline-powered passenger cars, vans, and light trucks. Compatible with engines from European, Japanese, and American manufacturers.

### **Features & Benefits**

- Low oil consumption and high thermal stability
- Superior wear protection and cleaner engine
- Enhanced oxidation and corrosion resistance
- Smooth engine operation in hot and cold conditions
- Optimized for fuel efficiency and reduced emissions

### **Meets & Exceeds Requirements Of:**

API SN, ACEA A3/B4, BMW Special Oil, VW 501 01, VW 505 00, MB 229.1, MB 229.3, PSA B712300, RN700, RN710

### **Typical Properties**

Property	Test Methods	Typical Value
SAE Grade		<b>10W-40</b>
Viscosity @ 100°C (cSt)	ASTM D445	<b>17.66</b>
Viscosity @ 40°C (cSt)	ASTM D445	<b>127.8</b>
Viscosity Index	ASTM D2270	<b>161</b>
Pour Point (°C)	ASTM D97	<b>-39</b>
Flash Point (°C)	ASTM D92	<b>220</b>
TBN (mg KOH/g)	ASTM D2896	<b>7.98</b>
Density @ 15°C (g/cm <sup>3</sup> )	ASTM D1298	<b>0.865</b>

### **Caution**

Avoid skin and eye contact. Wash skin thoroughly after handling it. Clean clothing before reusing. Repeated contact with used oil may cause skin irritation. Keep away from children. Prevent environmental pollution. Dispose of used oil properly.

