



GARUDA
LUBRICANTS

GARUDA CLUTCH & BRAKE FLUID DOT-3+

Product description

Garuda Brake Fluid DOT3 is a high boiling synthetic brake fluid which exceeds the requirements of SAE J1703, FMVSS 116 DOT 3, ISO 4925 and JIS K2233 specifications. It is designed for use in hydraulic brake systems of any commercial vehicles, passenger cars and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid.

Applications

Recommended for use in vehicles with conventional braking systems requiring poly glycol-based fluids. Compatible with all seals and metals used in standard brake systems. Ideal for on-road applications under normal to moderate load.

Features & Benefits

- Effective corrosion inhibitors provide long term corrosion protection for the metallic components of brake systems
- Provides lubrication and system protection
- Superior high temperature stability and low temperature fluidity ensure trouble-free operation
- Compatible with all standard seals and metals
-

Meets & Exceeds Requirements Of:

SAE J1703, FMVSS 116 DOT 3, ISO 4925, JIS K2233

Typical Properties

Property	Test Methods	Typical Value
SAE Grade		DOT-3+
Concentration wt%		100%
Freezing point °C @ (50% vol in water)	ASTM D1117	-36
Reflux boiling point °CC	ASTM D1120	160
pH (50% vol in water)	ASTM D1121	8.5
Density @ 15°C (g/cm ³)	ASTM D1298	1.12

Caution

All brake fluids should be kept clean and dry. Dirt or water contamination can affect performance and cause brake system failure. Brake fluids can affect vehicle paintwork, so remove spills immediately without rubbing. Keep out of reach of children. Dispose of fluid according to local environmental regulations.

